

DATA SHEETS

DECORATIVE COATINGS/TECHNICAL DATA SHEET

KUSASA ACRYLIC WATER PROOFING



GENERAL DATA

Description:	Kusasa Acrylic Water Proofing is a single pack system based on a soft styrene acrylic. The product is used in conjunction with water proofing membrane that is incorporated into the paint system.
Recommended Use	Water proofing compound for use on masonry surfaces, tiles and metal substrates.

TECHNICAL DATA

Specific Gravity:	1.28
Total Solids Content:	55% (+/- 2%)
Pigment Volume Concentration:	Approximately 25%
Theoretical Spreading Rate:	Approximately 6-8m ² / litre
Viscosity:	110Ku (Approximately)
Heat Stability (40hr@60°C):	Pass
Freeze Thaw Stability:	Pass - (40hrs @ -5°C)
Polymer Type:	Soft Styrene Acrylic
Touch Dry (hours):	2 hrs
Dry to Recoat Time (hours):	4 - 6hrs
Hard Dry (Days):	7
Colours:	White, Pink & Grey

APPLICATION DATA

Application Method:	Brush, Roller application.
Thinning (volume):	Not recommended
Thinner / Cleaner:	Water
Mixing Ratio:	N/A
Pot Life:	N/A

RECOMMENDED SYSTEM

Primer:	1 coat Kusasa Solvent Based Sealer
Water Proofing:	2 coats Acrylic Waterrproofing (roll membrane into first coat
Top Coats:	1-2 coats Kusasa Sheen Paint / Roof Paint

MISCELLANEOUS

Flash Point:	Water Based
Shelf Life:	6 months in original sealed containers under correct storage conditions

Note: We intend this publication to inform you about current practice without warrenty. Information on the use of our products must be tested to local conditions before application.

Telephone +27 (0) 31 464 8178, Facsimile +27 (0) 31 464 8179, E-mail info@kusasapaints.co.za