

DATA SHEETS

DECORATIVE COATINGS/TECHNICAL DATA SHEET

KUSASA ASPHALT SHIELD



GENERAL DATA

Description:	Kusasa Asphalt Shield is a premium quality water based pure acrylic paint designed to overcoat new & old asphalt driveways. The product being a pure acrylic will seal all asphalt surfaces . The product is supplied in Asphalt Black that on application will revive the appearance of the asphalt.
Recommended Use	Recommended for use on asphalt driveways. Kusasa Asphalt Shield will seal all asphalt surfaces and offer added UV protection to the substrate. 1-2 coats on Kusasa Asphalt Shield will give asphalt surfaces a uniform enhanced appearance with excellent colour fastness.

TECHNICAL DATA

Specific Gravity:	1.32
Volume Solids:	52% (+/- 1%)
Finish:	High sheen finish.
Theoretical Spreading Rate:	Dependant on substrate
Opacity:	Excellent
Reflectance:	93.70%
Drying Time:	The temperature, humidity, air movement and film thickness will affect the drying time.
Touch Dry (hours):	1 hours
Dry to Recoat Time (hours):	4 hours
Hard Dry (Days):	7
Colours:	Asphalt Black
Polymer Type:	100% Pure Acrylic

APPLICATION DATA

Application Method:	Brush, Roller or Spray application.
Thinning (volume):	Up to 40% dilution with water - dependant on the age of the asphalt to be treated
Thinner / Cleaner:	Water
Pot Life:	N/A

RECOMMENDED SYSTEM

Primer:	No primer recommended
Finishing:	1 - 2 coats Kusasa Asphalt Shield.

MISCELLANEOUS

Flash Point:	Water Based
Shelf Life:	12 months in original sealed containers under correct storage conditions

Note: We intend this publication to inform you about current practice without warrenty. Information on the use of our products must be tested to local conditions before application.

Telephone +27 (0) 31 464 8178, Facsimile +27 (0) 31 464 8179, E-mail info@kusasapaints.co.za