

DATA SHEETS

CEMENT PRODUCTS/TECHNICAL DATA SHEET

KUSASA CHEM BOND



GENERAL DATA

Description:

Chem Bond is a synthetic latex based additive specifically developed for use with Patching Compound where the product needs to be waterproofed. In addition the adhesion & flexibility of the product is increased.

Recommended Use

Where extra waterproofing/adhesion properties are required the water intake must be replaced with Chem Bond.

TECHNICAL DATA

Specific Gravity:	1.0
Volume Solids:	16%
Solubility:	Miscible in water
Theoretical Spreading Rate:	Approximatly 8-10 m ² / litre
Odour:	Minimum odour
Opacity:	Clear solution
Boiling Point:	Calculated as water 100°C
Viscosity:	1200cps
Dry to Overcoat Time (hours):	12 Hours
Hard Dry (Days):	N/A
Colours:	Clear solution
Polymer Type:	Styrene (latex)

APPLICATION DATA

Mixing Instructions:	Mix 1.75 litres of Chem Bond to 5kg/Patching Compound. Slowly add the powder to the liquid, stirring continiously until a smooth, lump free mixture is applied. Do not add additional water.
-----------------------------	--

RECOMMENDED SYSTEM

Primer:	N/A
Finishing:	N/A

MISCELLANEOUS

Flash Point:	Water Based
Shelf Life:	6 months in original sealed containers under correct storage conditions

Note: We intend this publication to inform you about current practice without warrenty. Information on the use of our products must be tested to local conditions before application.

Telephone +27 (0) 31 464 8178, Facsimile +27 (0) 31 464 8179, E-mail info@kusasapaints.co.za