

DATA SHEETS

CEMENT PRODUCTS/TECHNICAL DATA SHEET

KUSASA CHEM GRIP - PLASTER GRIP



GENERAL DATA

Description:

Chem Grip is a vinyl acetate emulsion primer used to aid the adhesion of cement plaster onto difficult substrates like smooth concrete, cement fibre board and weather board. The difficult substrates are primed with Chem Grip immediately prior to the cement plaster/skimming compound being applied.

Recommended Use

Chem Grip is applied to smooth surfaces of concrete, weather board, cement fibre board to aid the adhesion of the cement plaster/skimming compound to the substrate. Chem Grip is applied using a block brush.

TECHNICAL DATA

Specific Gravity:	1.0
Volume Solids:	25%
Solubility:	Miscible in water
Theoretical Spreading Rate:	Approximatly 8-10 m ² / litre
Odour:	Minimum odour
Opacity:	Clear solution
Boiling Point:	Calculated as water 100°C

Viscosity:	1400cps
Dry to Overcoat Time (hours):	N/A
Hard Dry (Days):	N/A
Colours:	Clear solution
Polymer Type:	Vinyl Acetate

APPLICATION DATA

Mixing Instructions:	Use Chem Grip as supplied. Do not add water to the mixture.
----------------------	---

RECOMMENDED SYSTEM

Primer:	N/A
Finishing:	N/A

MISCELLANEOUS

Flash Point:	Water Based
Shelf Life:	3 months in original sealed containers under correct storage conditions

Note: We intend this publication to inform you about current practice without warrenty. Information on the use of our products must be tested to local conditions before application.

Telephone +27 (0) 31 464 8178, Facsimile +27 (0) 31 464 8179, E-mail info@kusasapaints.co.za