

DATA SHEETS

CEMENT PRODUCTS/TECHNICAL DATA SHEET

KUSASA CHEM KOTE - CEMENT BASED PAINT



GENERAL DATA

Description:

Kusasa Chem Kote is a budget quality cement based paint that comprises of a composition of grey portland cement, sand, pigments & limited cement modifiers. Chem Kote is supplied in a powder form and mixed with water prior to application. The product once cured dries to a hard finish

Recommended Use

The paint is applied to off shutter concrete, cement plaster, flush brickwork, cement fibre board in exterior applications only. The product is applied using a block brush. Once applied Chem Kote has to be cured after 24 hours of application by wetting the surface 3 times a day at 4 hour intervals.

TECHNICAL DATA

Bulk Density

1.5

Volume Solids:

Powder based

Mixing Instructions:

Mix Chem Kote with water at the ratio of 8-10lt of water to 20kg of Chem Kote. Always add powder to liquid and mix constituents to a consistent creamy texture. Allow the product to stand for 10 minutes to allow the product to thicken and re-mix before use.

Pack Sizes:

20kg

Dry to Overcoat Time (hours):

12 hours

Colours:

Limited colour range

APPLICATION DATA

Application Method:

Apply product using a stiff block brush. Complete wall application from corner to corner in one application to avoid colour inconsistency

Cleaner:

Water

Mixing Ratio:

8-10lt water to 20kg Chem Kote

Pot Life:

2 hours

RECOMMENDED SYSTEM

Primer:

Non - Applicable

Finishing:

Non - Applicable

MISCELLANEOUS

Flash Point:

Powder based

Shelf Life:

3 months in original sealed packaging under correct storage conditions

Note: We intend this publication to inform you about current practice without warranty. Information on the use of our products must be tested to local conditions before application.

Telephone +27 (0) 31 464 8178, Facsimile +27 (0) 31 464 8179, E-mail info@kusasapaints.co.za