

DATA SHEETS

CEMENT PRODUCTS/TECHNICAL DATA SHEET

KUSASA CHEM PLUS - CEMENT BASED PAINT



GENERAL DATA

Description: Kusasa Chem Plus is an excellent quality cement based paint that comprises of a composition of white portland cement, sand, pigments & cement modifiers that enhance the product. Chem Plus is supplied in a powder form and mixed with water prior to application. For increased adhesion and water resistance replace the water with Chem Add.

Recommended Use The paint is applied to off shutter concrete, cement plaster, flush brickwork, cement fibre board using a block brush. Once applied Chem plus dries to a hard finish. When using Chem Add with Chem Plus the risk of efflorescence is greatly reduced.

TECHNICAL DATA

Bulk Density 1.5
Volume Solids: Powder based
Mixing Instructions: Mix Chem Plus with water at the ratio of 8-10lt of water to 20kg of Chem Plus. Always add powder to liquid and mix constituents to a consistent creamy texture. Allow the product to stand for 10 minutes to allow the product to thicken and re-mix before use. For increased adhesion requirements (in cases of poor substrate) and water resistance replace the water in the mix with Chem Add.

Pack Sizes: 20kg
Dry to Overcoat Time (hours): 12 hours

Colours: Standard colour range.

APPLICATION DATA

Application Method: Apply product using a stiff block brush. Complete wall application from corner to corner in one application to avoid colour inconsistency

Cleaner: Water
Mixing Ratio: 8-10lt water to 20kg Chem Plus
Pot Life: 2 hours

RECOMMENDED SYSTEM

Primer: Non - Applicable

Finishing: Non - Applicable

MISCELLANEOUS

Flash Point: Powder based
Shelf Life: 3 months in original sealed bags under correct storage conditions

Note: We intend this publication to inform you about current practice without warranty. Information on the use of our products must be tested to local conditions before application.

Telephone +27 (0) 31 464 8178, Facsimile +27 (0) 31 464 8179, E-mail info@kusasapaints.co.za