

DATA SHEETS

DECORATIVE COATINGS/TECHNICAL DATA SHEET

KUSASA CRACK FILLER

GENERAL DATA

Description & Use :

Kusasa Ready Mixed Crack Filler formulated to fill cracks, holes etc. in plastered walls in both an interior and exterior application. The product is both mould resistant and waterproofed. The product however is not suitable for use on surfaces that will be permanently submersed in water, nor is the crack filler suitable for use on structural cracks or cracks in excess of 6mm. The crack filler once dry must be sanded flush with the existing substrate. It is important to sand the crack filler within 24 hours of being applied. Any further delays will prove to be more difficult to sand.

TECHNICAL DATA

Specific Gravity:	Paste
Volume Solids:	75% to 80%
Finish:	Matt finish
Theoretical Spread Rate	Dependant upon size of the crack to be filled
Drying Time:	8-12 hours – The temperature, humidity air movement and product thickness will affect drying time
Dry to Recoat Time (hours):	Non - Applicable
Hard Dry (Days):	7
Colour:	White
Polymer Type:	Modified Styrene Acrylic

APPLICATION DATA

Application Method:	Trowel Application or Scraper
Thinning (volume):	Not recommended
Thinner / Cleaner:	Water
Mixing Ratio:	N/A
Pot Life:	N/A

RECOMMENDED SYSTEM

Primer:	Non - Applicable
Finishing:	Non - Applicable

MISCELLANEOUS

Flash Point:	Water Based
Shelf Life:	6 months

SAFETY

In the event of skin and or eye contamination wash affected areas immediately with clean water. Should any irritations persist Seek medical assistance

Note: We intend this publication to inform you about current practice without warrenty. Information on the use of our products must be tested to local conditions before application.

Telephone +27 (0) 31 464 8178, Facsimile +27 (0) 31 464 8179, E-mail info@kusasapaints.co.za