

DATA SHEETS

DECORATIVE COATINGS/TECHNICAL DATA SHEET

KUSASA DECORATORS ACRYLIC



GENERAL DATA

Description:	Kusasa Decorators Acrylic is a good quality low cost water based paint. Good hiding opacity with average scrubs resistance (+/- 1 000 cycles).
Recommended Use	Matt finish for use on masonry surfaces in both interior & exterior applications.

TECHNICAL DATA

Specific Gravity:	1.4
Volume Solids:	55% (+/- 1%)
Finish:	Matt finish.
Theoretical Spreading Rate:	Approximatly 8-10 m ² / litre
Opacity:	0.975
Reflectance:	N/A
Drying Time:	The temperature, humidity, air movement and film thickness will affect the drying time.
Touch Dry (hours):	1 hours
Dry to Recoat Time (hours):	4 hours
Hard Dry (Days):	7
Colours:	Available in white and pastel colours only
Polymer Type:	Styrene Acrylic

APPLICATION DATA

Application Method:	Brush or roller application.
Thinning (volume):	Not Applicable
Thinner / Cleaner:	Water
Mixing Ratio:	N/A
Pot Life:	N/A

RECOMMENDED SYSTEM

Finishing:	2-3 coats Kusasa Decorators Acrylic
-------------------	-------------------------------------

MISCELLANEOUS

Flash Point:	Water Based
Shelf Life:	6 months in original sealed containers under correct storage conditions

Note: We intend this publication to inform you about current practice without warrenty. Information on the use of our products must be tested to local conditions before application.

Telephone +27 (0) 31 464 8178, Facsimile +27 (0) 31 464 8179, E-mail info@kusasapaints.co.za