

DATA SHEETS

DECORATIVE COATINGS/TECHNICAL DATA SHEET

KUSASA FAST DRYING HIGH GLOSS ENAMEL



GENERAL DATA

Description:	A premium quality synthetic alkyd based quick drying high gloss enamel. The paint is durable & resistant to moderate atmospheric conditions. Good adhesion and opacity. Excellent re-coatability properties.
Recommended Use	Can be used on prepared substrates of masonry, steel and wood. Quick drying.

TECHNICAL DATA

Specific Gravity:	1.05
Volume Solids:	55% (+/- 1%)
Opacity:	Excellent
Theoretical Spreading Rate:	Approximately 8-10 m ² / litre
Recommended DFT:	30-40 microns (1 coat)
Resin Type:	Long Alkyd Oil
Drying Time:	The temperature, humidity, air movement and film thickness will affect the drying time.
Touch Dry (hours):	2 hours
Dry to Recoat Time (hours):	6-8 hours
Hard Dry (Days):	7
Colours:	Standard colours - White , Black, Red, Green, Brown Charcoal & Grey - Other colours available on request.

APPLICATION DATA

Application Method:	Brush, Roller or Spray application.
Thinning (volume):	10-15% dilution depending on application method
Thinner / Cleaner:	Turps / Thinners
Mixing Ratio:	N/A
Pot Life:	N/A

RECOMMENDED SYSTEM

Primer:	Kusasa General Purpose Undercoat - 1 coat
Finishing:	Kusasa Quick Drying High Gloss Enamel 1-2 coats

MISCELLANEOUS

Flash Point:	Solvent based
Shelf Life:	12 months in original sealed containers under correct storage conditions

Note: We intend this publication to inform you about current practice without warranty. Information on the use of our products must be tested to local conditions before application.

Telephone +27 (0) 31 464 8178, Facsimile +27 (0) 31 464 8179, E-mail info@kusasapaints.co.za