

DATA SHEETS

DECORATIVE COATINGS/TECHNICAL DATA SHEET

KUSASA FILLERCOAT



GENERAL DATA

Description:	Kusasa Decorators Acrylic is a good quality paint system for use on new walls of cured plaster. The particle size of the filler content is more coarse than general paints that fill voids left after plastering.
Recommended Use	Excellent primer for new walls of plaster and soffits in both internal & external applications. May be used as a finishing coat where an economic matt system is required.

TECHNICAL DATA

Specific Gravity:	1.4
Volume Solids:	60% (+/- 1%)
Finish:	Matt finish.
Theoretical Spreading Rate:	Approximatly 8 m ² / litre
Opacity:	Good
Reflectance:	Non - Applicable
Drying Time:	The temperature, humidity, air movement and film thickness will affect the drying time.
Touch Dry (hours):	1 hours
Dry to Recoat Time (hours):	4 hours
Hard Dry (Days):	7
Colours:	Available in white and pastel colours only
Polymer Type	Styrene Acrylic

APPLICATION DATA

Application Method:	Brush or roller application.
Thinning (volume):	Not Applicable
Thinner / Cleaner:	Water
Mixing Ratio:	N/A
Pot Life:	N/A

RECOMMENDED SYSTEM

Priming:	1 coat Kusasa Fillercoat
Finishing:	As specifiend

MISCELLANEOUS

Flash Point:	Water Based
Shelf Life:	6 months in original sealed containers under correct storage conditions

Note: We intend this publication to inform you about current practice without warrenty. Information on the use of our products must be tested to local conditions before application.

Telephone +27 (0) 31 464 8178, Facsimile +27 (0) 31 464 8179, E-mail info@kusasapaints.co.za