

DATA SHEETS

DECORATIVE COATINGS/TECHNICAL DATA SHEET

KUSASA FLOOR KOTE (SOLVENT BASED)



GENERAL DATA

Description:

A premium quality single pack floor coating manufactured using an urethane alkyd resin. The system gives excellent adhesion characteristics to universal applications. Good opacity & fast drying. Can be used on prepared substrates of masonry and wood.

Recommended Use

TECHNICAL DATA

Specific Gravity:	1.05
Volume Solids:	55% (+/- 1%)
Opacity:	Excellent
Theoretical Spreading Rate:	Approximately 8-10 m ² / litre
Recommended DFT:	30-40 microns (1 coat)
Resin Type:	Urethane Alkyd Oil
Drying Time:	The temperature, humidity, air movement and film thickness will affect the drying time.
Touch Dry (hours):	4 hours
Dry to Recoat Time (hours):	12 hours
Hard Dry (Days):	7
Colours:	White , Black, Red, Green, Brown, Charcoal & Grey

APPLICATION DATA

Application Method:	Brush, Roller or Spray application.
Thinning (volume):	10-15% dilution depending on application method
Thinner / Cleaner:	Turps / Thinners
Mixing Ratio:	N/A
Pot Life:	N/A

RECOMMENDED SYSTEM

Primer:	Dilute 1st coat with Turps
Finishing:	Kusasa Floor Kote 1-2 coats

MISCELLANEOUS

Flash Point:	Solvent based
Shelf Life:	12 months in original sealed containers under correct storage conditions

Note: We intend this publication to inform you about current practice without warranty. Information on the use of our products must be tested to local conditions before application.

Telephone +27 (0) 31 464 8178, Facsimile +27 (0) 31 464 8179, E-mail info@kusasapaints.co.za