

DATA SHEETS

DECORATIVE COATINGS/TECHNICAL DATA SHEET

KUSASA HIGH GLOSS ENAMEL



GENERAL DATA

Description:	A premium quality synthetic alkyd based high gloss enamel. The paint system is durable and resistant to moderate atmospheric conditions. The paint has excellent gloss levels, adhesion & opacity.
Recommended Use	Decorative finish coat for all interior and exterior applications onto surfaces of masonry, wood and metal.

TECHNICAL DATA

Specific Gravity:	1.06
Volume Solids:	55% (+/- 2%)
Resin Solids	35% (+/-2%)
Theoretical Spreading Rate:	Approximately 8-10 m ² / litre
Recommended DFT:	30-40 microns (1 coat)
Resin Type:	Long Alkyd Oil
Drying Time:	The temperature, humidity, air movement and film thickness will affect the drying time.
Touch Dry (hours):	1-3 hours
Dry to Recoat Time (hours):	12 hours
Hard Dry (Days):	7
Colours:	White, black, brown, yellow, green, grey, rustic red Tint bases available to tint spectrum of colours

APPLICATION DATA

Application Method:	Brush, Roller or Spray application.
Thinning (volume):	10-15% dilution depending on application method
Thinner / Cleaner:	Turps / thinners
Mixing Ratio:	N/A
Pot Life:	N/A

RECOMMENDED SYSTEM

Primer:	Kusasa Alkyd Undercoat - 1 coat or, Kusasa Plaster Primer - 1 coat
Finishing:	Kusasa Alkyd Enamel 1-2 coats

MISCELLANEOUS

Flash Point:	Solvent based
Shelf Life:	12 months in original sealed containers under correct storage conditions

Note: We intend this publication to inform you about current practice without warranty. Information on the use of our products must be tested to local conditions before application.

Telephone +27 (0) 31 464 8178, Facsimile +27 (0) 31 464 8179, E-mail info@kusasapaints.co.za