

DATA SHEETS

DECORATIVE COATINGS/TECHNICAL DATA SHEET

KUSASA PINK WOOD PRIMER



GENERAL DATA

Description:	A premium quality synthetic based alkyd primer for priming of wood. The paint system gives maximum enamel holdout and has good opacity. The primer may be overcoated with alkyd or acrylic top coats
Recommended Use	General purpose primer for wood.

TECHNICAL DATA

Specific Gravity:	1.28
Volume Solids:	50% (+/- 2%)
Resin Solids	15%
Theoretical Spreading Rate:	Approximately 8-10 m ² / litre
Recommended DFT:	30-40 microns (1 coat)
Resin Type	Medium Alkyd Oil
Drying Time:	The temperature, humidity, air movement and film thickness will affect the drying time.
Touch Dry (hours):	4
Dry to Recoat Time (hours):	12 hours
Hard Dry (Days):	7
Colours:	Pink

APPLICATION DATA

Application Method:	Brush, Roller or Spray application.
Thinning (volume):	10% dilution depending on application method
Thinner / Cleaner:	Turps / Thinners
Mixing Ratio:	N/A
Pot Life:	N/A

RECOMMENDED SYSTEM

Primer:	Kusasa Pink Wood Primer - 1 coat
Intermediate Coat:	Kusasa Universal Undercoat - 1 coat
Finishing:	Kusasa High Gloss/Eggshell Enamel 1-2 coats

MISCELLANEOUS

Flash Point:	Solvent based
Shelf Life:	12 months in original sealed containers under correct storage conditions

Note: We intend this publication to inform you about current practice without warranty. Information on the use of our products must be tested to local conditions before application.

Telephone +27 (0) 31 464 8178, Facsimile +27 (0) 31 464 8179, E-mail info@kusasapaints.co.za