

DATA SHEETS

DECORATIVE COATINGS/TECHNICAL DATA SHEET

KUSASA PLASTER PRIMER



GENERAL DATA

Description:	A premium quality synthetic alkyd based primer for use on new walls of plaster in both internal & external applications. The paint has good opacity. The paint must be overcoated with a topcoat.
Recommended Use	General purpose undercoat for use on all interior & exterior new walls of masonry

TECHNICAL DATA

Specific Gravity:	1.24
Volume Solids:	60% (+/- 1%)
Opacity:	Good
Theoretical Spreading Rate:	Approximately 8m ² / litre
Recommended DFT:	30-40 microns (1 coat)
Resin Type:	Medium Alkyd Oil
Drying Time:	The temperature, humidity, air movement and film thickness will affect the drying time.
Touch Dry (hours):	2 hours
Dry to Recoat Time (hours):	4-6 hours
Hard Dry (Days):	Non - Applicable
Colours:	White. Can be tinted on request - pastel & medium base colours only

APPLICATION DATA

Application Method:	Brush, Roller or Spray application.
Thinning (volume):	No dilution recommended
Thinner / Cleaner:	Turps
Mixing Ratio:	N/A
Pot Life:	N/A

RECOMMENDED SYSTEM

Primer:	KusasaPlaster Primer - 1 coat
Finishing:	As specified

MISCELLANEOUS

Flash Point:	Solvent based
Shelf Life:	6 months in original sealed containers under correct storage conditions

Note: We intend this publication to inform you about current practice without warranty. Information on the use of our products must be tested to local conditions before application.

Telephone +27 (0) 31 464 8178, Facsimile +27 (0) 31 464 8179, E-mail info@kusasapaints.co.za