

DATA SHEETS

DECORATIVE COATINGS/TECHNICAL DATA SHEET

KUSASA READY MIXED GROUT

GENERAL DATA

Description & Use :

Kusasa Ready Mixed Grout is ready to use acrylic based grout designed for use on wall tiles only. The grout is waterproofed and has anti-fungal properties. The product is not suitable for use on floor tiles.

The product must not be applied in any application where the product will be immersed under water (swimming pools etc.)

TECHNICAL DATA

Specific Gravity:	Paste
Volume Solids:	80%
Finish:	Matt finish
Coverage:	152mmx152mmx5mm with 2mm gap = 150ml/m ²
Opacity:	Non - Applicable
Reflectance:	Non - Applicable
Drying Time:	The temperature, humidity, air movement and thickness of the joint will affect the drying time.
Touch Dry (hours):	12 hours
Dry to Recoat Time (hours):	Non - Applicable
Hard Dry (Days):	7
Colours:	White, Light Grey
Polymer Type:	Styrene Acrylic

APPLICATION DATA

Application Method:	Grout Applicator
Thinning (volume):	No dilution recommended
Thinner / Cleaner:	Water
Mixing Ratio:	N/A
Pot Life:	N/A

RECOMMENDED SYSTEM

Primer:	Non - Applicable
Finishing:	Non - Applicable

MISCELLANEOUS

Flash Point:	Water Based
Shelf Life:	6 months in original sealed containers under correct storage conditions

Note: We intend this publication to inform you about current practice without warranty. Information on the use of our products must be tested to local conditions before application.

Telephone +27 (0) 31 464 8178, Facsimile +27 (0) 31 464 8179, E-mail info@kusasapaints.co.za

