

DATA SHEETS

DECORATIVE COATINGS/TECHNICAL DATA SHEET

KUSASA ROOF KOTE



GENERAL DATA

Description:	Kusasa Roof Kote is a premium quality water based roof paint. Product is manufactured using 100% pure acrylic polymer. Excellent durability, flexibility washability, & scrubs resistance (>20 000 cycles).
Recommended Use	Mid sheen roof coating for roof substrates of masonry, clay tile and asbestos

TECHNICAL DATA

Specific Gravity:	1.32
Volume Solids:	50% (+/- 1%)
Finish:	Mid Sheen finish.
Theoretical Spreading Rate:	Dependant on substrate
Opacity:	0.982
Reflectance:	Not Applicable
Drying Time:	The temperature, humidity, air movement and film thickness will affect the drying time.
Touch Dry (hours):	1 hours
Dry to Recoat Time (hours):	4 hours
Hard Dry (Days):	7
Colours:	Black, Charcoal, Brown, Terracotta, Rustic Red, Coral Tan and Fadeless Green
Polymer Type:	100% Pure Acrylic

APPLICATION DATA

Application Method:	Brush, Roller or Spray application.
Thinning (volume):	10% dilution with water for 1st coat application on unpainted cement roof tiles, or, when spraying
Thinner / Cleaner:	Water
Pot Life:	N/A

RECOMMENDED SYSTEM

Primer:	1 coat Solvent Based Sealer or Water Based Sealer on unpainted cement/clay roof tiles.
Finishing:	2 coats Kusasa Roof Kote.

MISCELLANEOUS

Flash Point:	Water Based
Shelf Life:	12 months in original sealed containers under correct storage conditions

Note: We intend this publication to inform you about current practice without warrenty. Information on the use of our products must be tested to local conditions before application.

Telephone +27 (0) 31 464 8178, Facsimile +27 (0) 31 464 8179, E-mail info@kusasapaints.co.za