

DATA SHEETS

DECORATIVE COATINGS/TECHNICAL DATA SHEET

KUSASA ROUND STIPPLE



GENERAL DATA

Description:	Kusasa Round Stipple is a coarse textured coating based on a soft styrene acrylic polymer. The painted coating exhibits excellent durability, flexibility & weather resistance with rounded stipple finish.
Recommended Use	Textured coating for interior & exterior surfaces of primed concrete, plaster, asbestos, gypsum and wood. Round stipple texture once cured has no sharp edges.

TECHNICAL DATA

Specific Gravity:	1.50
Volume Solids:	approx 70%
Finish:	Matt finish
Theoretical Spreading Rate:	1.5kg/m ²
Opacity:	Thick coating
Reflectance:	N/A
Drying Time:	The temperature, humidity, air movement and film thickness will affect the drying time.
Touch Dry (hours):	4-6 hours
Dry to Recoat Time (hours):	24 hours
Hard Dry (Days):	7
Colours:	Natural off white colour. Can be manufactured to a range of colours on request.
Polymer Type:	Styrene Acrylic

APPLICATION DATA

Application Method:	Foam Roller
Thinning (volume):	No dilution permitted
Thinner / Cleaner:	Water
Pot Life:	N/A

RECOMMENDED SYSTEM

Primer:	1 coat Solvent Based Sealer or Water Based Sealer
Finishing:	1 coat Kusasa Round Stipple - Overcoated with a wash coat of Kusasa Acrylic Sheen for washability.

MISCELLANEOUS

Flash Point:	Water Based
Shelf Life:	6 months in original sealed containers under correct storage conditions

Note: We intend this publication to inform you about current practice without warranty. Information on the use of our products must be tested to local conditions before application.

Telephone +27 (0) 31 464 8178, Facsimile +27 (0) 31 464 8179, E-mail info@kusasapaints.co.za