

DATA SHEETS

DECORATIVE COATINGS/TECHNICAL DATA SHEET

KUSASA SCRATCH KOTE - RESIN PLASTER



GENERAL DATA

Description:	Kusasa Scratch Kote is a trowel applied, high build textured resin plaster containing graded aggregate that produces a flat raked finish.
Recommended Use	Kusasa Scratch Kote is applied onto most masonry surfaces in both internal and external applications. May be applied onto treated wood. Scratch kote is available in 1mm, 1,6mm & 3mm variants.

TECHNICAL DATA

Specific Gravity:	1.6
Volume Solids:	70% (+/- 1%)
Finish:	Matt finish.
Theoretical Spreading Rate:	1.0mm Scratch Kote - 2.5kg/m ² 1.6mm Scratch kote - 3.2kg/m ² 3.0mm Scratch Kote - 4.5kg/m ²
Drying Time:	The temperature, humidity, air movement and film thickness will affect the drying time. At 25°C/RH65%.
Touch Dry (hours):	2 hours - At 25°C/RH65%.
Dry to Recoat Time (hours):	12 hours
Hard Dry (hours):	12 hours - At 25°C/RH65%.
Colours:	Colours manufactured on request
Composition	Inert pigments, fillers & additives dispersed in a Styrene Acrylic Polymer
Polymer Type:	Styrene Acrylic

APPLICATION DATA

Application Method:	Trowel
Thinning (volume):	10% dilution with water
Thinner / Cleaner:	Water
Pot Life:	N/A

RECOMMENDED SYSTEM

Primer:	1 coat Solvent Based Sealer
Finishing:	Overcoat Scratch Kote with 1 coat of Kusasa Glaze Coat / Acrylic Sheen (if colour required)

MISCELLANEOUS

Flash Point:	Water Based
Shelf Life:	6 months in original sealed containers under correct storage conditions

Note: We intend this publication to inform you about current practice without warrenty. Information on the use of our products must be tested to local conditions before application.

Telephone +27 (0) 31 464 8178, Facsimile +27 (0) 31 464 8179, E-mail info@kusasapaints.co.za