

DATA SHEETS

DECORATIVE COATINGS/TECHNICAL DATA SHEET

KUSASA SOLVENT BASED ALKALI RESISTANT SEALER



GENERAL DATA

Description:

A premium quality solvent based alkali resistant sealer. The active ingredient is carried in a high aromatic solvent to ensure maximum penetration of the substrate.

Recommended Use

for use in sealing surfaces of masonry, slasto, cement bricks, clay bricks, non-glazed ceramic tile, asbestos & gypsum.

TECHNICAL DATA

Specific Gravity:	1.00
Volume Solids:	15% (+/-1%)
Finish:	N/A
Theoretical Spreading Rate:	8-10m ² /litre - dependant however on absorbency of substate
Opacity:	Clear
Reflectance:	N/A
Drying Time:	The temperature, rate of absorbency, humidity & air movement will affect the drying time.
Touch Dry (hours):	1
Dry to Recoat Time (hours):	4-6 hours
Hard Dry (hours):	24
Colours:	Clear
Polymer Type:	Solution Polymer

APPLICATION DATA

Application Method:	Brush, roller or spray application.
Thinning (volume):	Xylene - as required to aid rate of absorption
Thinner / Cleaner:	Turps
Pot Life:	N/A

RECOMMENDED SYSTEM

Primer:	N/A
Finishing:	Minimum of 2 coats Kusasa Solvent Based Sealer

MISCELLANEOUS

Flash Point:	Solvent Based
Shelf Life:	12 months in original sealed containers under correct storage conditions

Note: We intend this publication to inform you about current practice without warrenty. Information on the use of our products must be tested to local conditions before application.

Telephone +27 (0) 31 464 8178, Facsimile +27 (0) 31 464 8179, E-mail info@kusasapaints.co.za