

DATA SHEETS

DECORATIVE COATINGS/TECHNICAL DATA SHEET

KUSASA STOEP PAINT



GENERAL DATA

Description:	A good quality floor paint manufactured using a blend of alkyd resins comprising of a long oil and urethane alkyd. The system gives adequate adhesion for low traffic applications. Good opacity & gloss levels.
Recommended Use	Can be used on prepared substrates of masonry.

TECHNICAL DATA

Specific Gravity:	1.2
Volume Solids:	50% (+/- 1%)
Opacity:	Good
Theoretical Spreading Rate:	Approximately 8m ² / litre
Recommended DFT:	30-40 microns (1 coat)
Resin Type:	Blend of Long & Urethane Alkyd Oils
Drying Time:	The temperature, humidity, air movement and film thickness will affect the drying time.
Touch Dry (hours):	4-6 hours
Dry to Recoat Time (hours):	12 hours
Hard Dry (Days):	7
Colours:	White, Black, Red, Green, Brown, Charcoal & Grey
Finish:	Gloss Finish

APPLICATION DATA

Application Method:	Brush, Roller or Spray application.
Thinning (volume):	10-15% dilution depending on application method
Thinner / Cleaner:	Turps / Thinners
Mixing Ratio:	N/A
Pot Life:	N/A

RECOMMENDED SYSTEM

Primer:	Kusasa General Purpose Undercoat - 1 coat
Finishing:	Kusasa Stoep Paint 1-2 coats

MISCELLANEOUS

Flash Point:	Solvent based
Shelf Life:	12 months in original sealed containers under correct storage conditions

Note: We intend this publication to inform you about current practice without warranty. Information on the use of our products must be tested to local conditions before application.

Telephone +27 (0) 31 464 8178, Facsimile +27 (0) 31 464 8179, E-mail info@kusasapaints.co.za