

DATA SHEETS

DECORATIVE COATINGS/TECHNICAL DATA SHEET

KUSASA SUPER ACRYLIC



GENERAL DATA

Description:	Kusasa Super Acrylic is a good quality water based paint. Product is manufactured using 100% pure acrylic polymer. Excellent durability, hiding opacity & scrubs resistance (>10 000 cycles).
Recommended Use	Matt finish for use on masonry surfaces in both interior & exterior applications.

TECHNICAL DATA

Specific Gravity:	1.4
Volume Solids:	55% (+/- 1%)
Finish:	Matt sheen finish.
Theoretical Spreading Rate:	Approximately 8-10 m ² / litre
Opacity:	0.98
Reflectance:	Matt finish
Drying Time:	The temperature, air movement and film thickness will affect the drying time.
Touch Dry (hours):	1 hours
Dry to Recoat Time (hours):	4 hours
Hard Dry (Days):	7
Colours:	Tint bases available to tint all colours
Polymer Type:	100% Pure Acrylic

APPLICATION DATA

Application Method:	Brush, Roller or Spray application.
Thinning (volume):	10% dilution when spraying
Thinner / Cleaner:	Water
Mixing Ratio:	N/A
Pot Life:	N/A

RECOMMENDED SYSTEM

Primer:	1 coat Kusasa Alkyd Undercoat, Plaster Primer, Solvent Based Sealer, Water Based Sealer or Kusasa Fillercoat
Finishing:	2 coats Kusasa Super Acrylic

MISCELLANEOUS

Flash Point:	Water Based
Shelf Life:	6 months in original sealed containers under correct storage conditions

Note: We intend this publication to inform you about current practice without warranty. Information on the use of our products must be tested to local conditions before application.

Telephone +27 (0) 31 464 8178, Facsimile +27 (0) 31 464 8179, E-mail info@kusasapaints.co.za