

DATA SHEETS

DECORATIVE COATINGS/TECHNICAL DATA SHEET

KUSASA WATER BASED SEALER



GENERAL DATA

Description:	A premium quality water based sealer based on a soft styrene acrylic polymer.
Recommended Use	For use in sealing previously applied chalking paint in both internal & exterior applications

TECHNICAL DATA

Specific Gravity:	1.00
Volume Solids:	25% (+/-1%)
Finish:	N/A
Theoretical Spreading Rate:	8-10m ² /litre - dependant however on absorbency of substrate
Opacity:	Clear
Reflectance:	N/A
Drying Time:	The temperature, rate of absorbency, humidity & air movement will affect the drying time.
Touch Dry (hours):	1
Dry to Recoat Time (hours):	1 hour
Hard Dry (hours):	24
Colours:	Clear
Polymer Type:	Styrene Acrylic

APPLICATION DATA

Application Method:	Brush, roller or spray application.
Thinning (volume):	Not permitted
Thinner / Cleaner:	Water
Pot Life:	N/A

RECOMMENDED SYSTEM

Primer:	N/A
Finishing:	Apply 1 coat of Kusasa Water Based Sealer

MISCELLANEOUS

Flash Point:	Water based
Shelf Life:	3-6 months in original sealed containers under correct storage conditions

Note: We intend this publication to inform you about current practice without warranty. Information on the use of our products must be tested to local conditions before application.

Telephone +27 (0) 31 464 8178, Facsimile +27 (0) 31 464 8179, E-mail info@kusasapaints.co.za