

DATA SHEETS

DECORATIVE COATINGS/TECHNICAL DATA SHEET

KUSASA WEATHERTEX COARSE



GENERAL DATA

Description:

Kusasa Weathertex Coarse is a coarse textured coating based on a soft styrene co-polymer emulsion. The inclusion of mica enhances the durability, flexibility and weather resistance.

Recommended Use

Coarse textured coating for interior & exterior surfaces of primed concrete, plaster, asbestos, gypsum and primed wood. Weathertex coarse when applied with a foam roller will result in a soft round stipple finish.

TECHNICAL DATA

Specific Gravity:	1.40
Volume Solids:	approx 60%
Finish:	Matt finish
Theoretical Spreading Rate:	5m ² /lt
Opacity:	Thick coating
Reflectance:	N/A
Drying Time:	The temperature, humidity, air movement and film thickness will affect the drying time.
Touch Dry (hours):	4-6 hours
Dry to Recoat Time (hours):	24 hours
Hard Dry (Days):	7
Colours:	Natural off white colour. Can be manufactured to a range of colours on request.
Polymer Type:	Styrene Acrylic

APPLICATION DATA

Application Method:	Foam Roller - stipple finish / lambs wool - flat finish
Thinning (volume):	No dilution permitted
Thinner / Cleaner:	Water
Pot Life:	N/A

RECOMMENDED SYSTEM

Primer:	1 coat Solvent Based Sealer or Water Based Sealer
Finishing:	1-2 coats Kusasa Weathertex Coarse - Overcoated with a wash coat of Kusasa Acrylic Sheen for washability.

MISCELLANEOUS

Flash Point:	Water Based
Shelf Life:	6 months in original sealed containers under correct storage conditions

Note: We intend this publication to inform you about current practice without warranty. Information on the use of our products must be tested to local conditions before application.

Telephone +27 (0) 31 464 8178, Facsimile +27 (0) 31 464 8179, E-mail info@kusasapaints.co.za